



EN 12150-2:2004



OAKLAND GLASS LTD  
QUALITY AT THE HEART OF OUR GLASS

GLASS IN BUILDING  
THERMALLY TOUGHENED SODA LIME SILICATE SAFETY GLASS  
INTENDED TO BE USED IN BUILDING AND CONSTRUCTION WORKS

# DECLARATION OF PERFORMANCE

THIS IS TO CERTIFY THAT

**OAKLAND GLASS LIMITED**

of

Bretfield Court

Bretton Street Industrial Estate

Savile Town

Dewsbury

West Yorkshire

WF12 9BG

HAVE CONFORMED WITH EN 12150-2 ANNEX ZA

by

SUBMITTING GLASS' FOR INITIAL TYPE TESTING TO EN 12150-1, EN 1288-3 AND EN 12600


TESTING TO:	NOTIFIED TEST HOUSE	PRODUCTS	TEST REPORT No's
EN 12150-1	BSI Product Services Limited	CLEAR, OBSCURE, ENAMELLED AND SOFT & HARD COAT GLASS'	2624903721
EN 1288-3	BSI Product Services Limited	CLEAR AND SOFT & HARD COAT GLASS'	2624903721
EN 12600	BSI Product Services, Wintech Engineering Limited	CLEAR, OBSCURE, ENAMELLED AND SOFT & HARD COAT GLASS'	2624654484, R160058, R160059, R160060

INSTIGATING AND IMPLEMENTING A SYSTEM OF FACTORY PRODUCTION CONTROL COMPLYING WITH BS EN 12150-2:2004

PRODUCING A TECHNICAL FILE CONTAINING THE TEST REPORTS AND PERFORMANCE INDICATION PAPERS FOR ALL COMPONENTS



Signed: *M. B. Stolar*  
Position: *Managing Director*



OAKSOFT  
ENERGY SAVER

Company Reg. No. 2036622  
V.A.T. Reg. No. 427 5976 12

Oakland Glass Limited  
Bretfield Court • Bretton Street Industrial Estate • Dewsbury • West Yorkshire • WF12 9BG  
T. 01924 463198 • F. 01924 454931 • E. info@oaklandglass.co.uk  
www.oaklandglass.co.uk



OAKLAND GLASS LTD  
QUALITY AT THE HEART OF OUR GLASS

OAKLAND GLASS LIMITED

Bretfield Court

Bretton Street Industrial Estate

Saville Town

Dewsbury

West Yorkshire

WF12 9BG

EN 1279-5

Insulated glass units, intended to be used in buildings and construction works

System: 4mm Clear - 16 or 20mm Spacer Argon - 4mm Soft Coat

Characteristics


Resistance to fire	npd
Reaction to fire	A1
External fire performance	npd
Bullet resistance	npd
Explosion resistance	npd
Burglar resistance	npd
Pendulum body impact resistance	npd
Resistance against sudden temperature changes and temperature differentials	≥ 40+40K
Wind, snow permanent and imposed load resistance	≥ 4+4 mm
Direct airborne sound insulation	npd
Thermal properties	1.2W/(m²K)

Radiation properties:

light transmission and reflection	npd
solar energy characteristics	npd

Hazardous Substances None

Signed: *M. Babalau*  
Position: *Managing Director*



OAKSOFT  
ENERGY SAVER

Oakland Glass Limited  
Bretfield Court • Bretton Street Industrial Estate • Dewsbury • West Yorkshire • WF12 9BG  
T. 01924 463198 • F. 01924 454931 • E. info@oaklandglass.co.uk

www.oaklandglass.co.uk

Company Reg. No. 2036622  
V.A.T. Reg. No. 427 5976 12